

EGYPTENE HD 5502 GA

High Density Polyethylene
Sidpec (Sidi Kerir Petrochemicals Co.)

Message:

HD 5502 GA is a medium molecular weight copolymer grade with a broad molecular weight distribution, which offers an optimum balance of properties for use in a wide range of blow moulded applications.

GA: Gas phase process.

General Information			
Features	Copolymer		
	Good Processability		
	High ESCR (Stress Crack Resist.)		
	High Rigidity		
	Medium Impact Resistance		
	Medium Molecular Weight		
	Wide Molecular Weight Distribution		
Uses	Blow Molding Applications		
	Containers		
	Household Goods		
	Packaging		
	Piping		
Agency Ratings	EU No 10/2011		
Forms	Pellets		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.955	g/cm ³	ISO 1872-1
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.20	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	25.0	MPa	Internal Method
Tensile Strain (Break)	1000	%	Internal Method
Flexural Modulus	1000	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Impact Resistance - F50	330.00	cm	Internal Method
Bottle Stress Crack Resistance (50°C)	1.0	day	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

