

Geon™ Vinyl Flexible B65F1

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Flexible B65F1 is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Construction Applications. Primary characteristic: flame retardant.

General Information			
Features	Flame Retardant		
	Good Melt Strength		
Uses	Construction Applications		
Forms	Pellets		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	65		
Shore A, 15 sec	57		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹			ASTM D638
Break	10.3	MPa	
100% Strain	3.62	MPa	
Tensile Elongation ² (Break)	460	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength ³	38.5	kN/m	ASTM D624
Compression Set (23°C, 22 hr)	22	%	ASTM D395
Clash-Berg Modulus			ASTM D1043
--	24.1	MPa	
-55°C	310	MPa	
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-51.1	°C	ASTM D746
Injection	Nominal Value	Unit	
Processing (Melt) Temp	188 to 199	°C	
Extrusion	Nominal Value	Unit	
Melt Temperature	168 to 174	°C	
NOTE			

1.	510 mm/min
2.	510 mm/min
3.	Die C, 510 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

