

Hostacom PPU X9067HS Natural

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hostacom PPU X9067HS Natural is a medium high flow, medium flexural modulus mineral filled HCPP copolymer with high toughness. It is used for automotive interior trim applications.

General Information	
Filler / Reinforcement	Mineral
Features	Good Flow
	Good Stiffness
	Good Toughness
	Highly Crystalline
Uses	Automotive Interior Parts
	Automotive Interior Trim

Physical	Nominal Value	Unit	Test Method
Density	0.910	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	14	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	22.0	MPa	ISO 527-2/50
Tensile Strain (Yield)	4.0	%	ISO 527-2/50
Flexural Modulus - Chord (23°C)	1300	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	8.0	kJ/m ²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT