

EPAMOULD 290A10

Thermoplastic Polyurethane Elastomer (Polyester)

Epaflex Polyurethanes S.R.L.

Message:

EPAMOULD 290A10 is a thermoplastic polyurethane elastomer (polyester)(TPU-polyester) product. It can be processed by injection molding and is available in Europe.

Features include:

High Flexibility

high strength

accessible food

General Information		
Additive	Beeswax	
Features	High Flexibility	
	High strength	
	Hydrolysis resistance	
	Compliance of Food Exposure	
Appearance	Clear/transparent	
Processing Method	Injection molding	
Physical	Nominal Value	Unit
Density	1.19	g/cm ³
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	90	
Mechanical	Nominal Value	Unit
Abrasion Loss	35.0	mm ³

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT