Resinoid 1310

Phenolic

Resinoid Engineering Corporation

Message:

Resinoid 1310 is a Phenolic product filled with glass fiber and mineral. It can be processed by compression molding, injection molding, or resin transfer molding and is available in North America. Applications of Resinoid 1310 include automotive and electrical/electronic applications.

Characteristics include:

Flame Rated Heat Resistant

Impact Resistant

General Information			
UL YellowCard	E61847-247048		
Filler / Reinforcement	Glass Fiber		
	Mineral		
Features	Good Impact Resistance		
	Good Thermal Stability		
Uses	Automotive Exterior Parts		
	Electrical Parts		
Appearance	Black		
Forms	Pellets		
Processing Method	Compression Molding		
	Injection Molding		
	Resin Transfer Molding		

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.81	g/cm³	ASTM D792
Bulk Factor	2.0		ASTM D1895
Molding Shrinkage - Flow	0.10 to 0.20	%	ASTM D955
Water Absorption (24 hr)	0.20	%	ASTM D570
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	55.2	MPa	ASTM D638
Flexural Modulus	17200	MPa	ASTM D790
Flexural Strength (Yield)	110	MPa	ASTM D790
Compressive Strength	207	MPa	ASTM D695
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	53	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method

Deflection Temperature Under Load (1.8					
MPa, Unannealed)	316	°C	ASTM D648		
Electrical	Nominal Value	Unit	Test Method		
Dielectric Strength	9.4	kV/mm	ASTM D149		
Arc Resistance	180	sec	ASTM D495		
Flammability	Nominal Value	Unit	Test Method		
Flame Rating	V-0		UL 94		
Injection	Nominal Value	Unit			
Processing (Melt) Temp	149 to 177	°C			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

