

Shandong PP KPP30-1

Polypropylene

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PP KPP30-1 is a Polypropylene material filled with mineral. It is available in Asia Pacific. Primary attribute of Shandong PP KPP30-1: Rigid.
Typical applications include:
Appliances
Automotive
Electrical/Electronic Applications

General Information		
Filler / Reinforcement	Mineral	
Features	High Rigidity	
Uses	Appliance Components	
	Automotive Applications	
	Electrical/Electronic Applications	

Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	> 25.0	MPa
Flexural Stress	> 30.0	MPa

Impact	Nominal Value	Unit
Notched Izod Impact Strength	> 4.0	kJ/m ²
Unnotched Izod Impact Strength	> 35	kJ/m ²

Thermal	Nominal Value	Unit
Heat Deflection Temperature (0.45 MPa, Unannealed)	> 100	°C

Additional Information	Nominal Value	Unit
Residue of Combustion	28 to 32	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT