DIGITALWAX® DS 3000

Unspecified

DWS Systems

Message:

Photosensitive Resin for DigitalWax® D Series Stereolithography Systems

DS 3000 Bio-Compatible resin is specially developed for production of high precision surgical guide as dental drill guides and all the applications that requires a limited contact with the body. It works directly from intraoral digital capture devices, as a replacement of the traditional physical ones. Features

Smooth surface High resolution High accuracy Durable

Transparent

General Information		
Features	Biocompatible	
	Durable	
	Good Surface Finish	
Uses	Dental Applications	
	Medical Devices	
	Medical/Healthcare Applications	
Appearance	Transparent - Slight Yellow	
Forms	Liquid	
Processing Method	3D Printing, Stereolithography	
Physical	Nominal Value	Unit
Viscosity ¹ (25°C)	600 to 800	mPa·s
Hardness	Nominal Value	Unit
Durometer Hardness (Shore D)	87	
Mechanical	Nominal Value	Unit
Tensile Modulus	1340	MPa
Tensile Strength	30.0	MPa
Tensile Elongation (Break)	7.0	%
Flexural Modulus	2110	MPa
Flexural Strength	94.6	MPa
Thermal	Nominal Value	Unit
Deflection Temperature Under Load (0.45 MPa, Unannealed)	55.0	°C
NOTE		
1.	Liquid Resin	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

