# CYCOLAC<sup>™</sup> INP108 resin

## Acrylonitrile Butadiene Styrene

### SABIC Innovative Plastics

#### Message:

SABIC INP108 is a high rubber ABS impact modifier resin, and is based on polybutadiene rubber. Offers superior impact efficiency, especially at low temperatures. Reduces notch sensitivity when alloyed with engineering polymers. Disperses easily. Provides abrasion and chemical resistance to polymers.

| General Information      |                                   |       |                 |
|--------------------------|-----------------------------------|-------|-----------------|
| Additive                 | Rubber Impact Modifier            |       |                 |
| Features                 | Dispersible                       |       |                 |
|                          | Good Abrasion Resistance          |       |                 |
|                          | Good Chemical Resistance          |       |                 |
|                          | Low Temperature Impact Resistance |       |                 |
|                          |                                   |       |                 |
| Uses                     | Blending                          |       |                 |
| Physical                 | Nominal Value                     | Unit  | Test Method     |
| Specific Gravity         |                                   |       |                 |
|                          | 0.998                             | g/cm³ | ASTM D792       |
| 1                        | 1.01                              | g/cm³ | ISO 1183        |
| Apparent Density         | 0.35                              | g/cm³ | ASTM D1895      |
| Mean Particle Size       | 400.0                             | μm    | Internal Method |
| Rubber Content           | 32                                | %     | Internal Method |
| Total NA Volatiles       | 0.10                              | %     | Internal Method |
| Hardness                 | Nominal Value                     | Unit  | Test Method     |
| Shore Hardness (Shore D) | 58                                |       | ISO 868         |
| NOTE                     |                                   |       |                 |
| 1.                       | Molded                            |       |                 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

