

# ELASTEL™ CP-SE1-R1

Chlorinated Polyethylene  
HELLENIC CABLES S.A.

Message:

Description: CPE (Chlorinated Polyethylene) based compounds for sheaths in elastic power cables  
Specifications: TYPE SE1, BS 6899 Type RS2  
Packaging: In carton boxes of approximately 400-1000 kg

General Information		
Uses	Wire & Cable Applications	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.33	g/cm³
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	55.0	°C
Cylinder Zone 2 Temp.	60.0	°C
Cylinder Zone 3 Temp.	60.0	°C
Head Temperature	65	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT