

Akulon® F-X9182

Polyamide 6
DSM Engineering Plastics

Message:

Akulon® F-X9182 is a Polyamide 6 (Nylon 6) material. It is available in Asia Pacific or Europe for film extrusion. Primary attribute of Akulon® F-X9182: Medium Viscosity.
Typical application of Akulon® F-X9182: Film

General Information			
Features	Medium-low Viscosity		
Uses	Film		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.13	g/cm³	ISO 1183
Viscosity Number	160	cm³/g	ISO 307
Thermal	Nominal Value	Unit	Test Method
CLTE - Flow	9.0E-5	cm/cm/°C	ISO 11359-2
Additional Information	Nominal Value	Test Method	
RSV ¹	2.60	Internal Method	
NOTE			
1.	Formic Acid, 1g/100 ml		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT