ADMER™ QB510A

Polypropylene

Mitsui Chemicals America, Inc.

Message:

ADMER™ QB510A is a Polypropylene material. It is available in North America for blown film or cast film.

Typical applications include:

Adhesives/Tapes

Bottles

Plumbing/Piping/Potable Water

General Information			
Uses	Adhesives		
	Bottles		
	Piping		
Forms	Pellets		
Processing Method	Blown Film		
	Cast Film		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	3.3	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

°C

ASTM D1525

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

142

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

Vicat Softening Temperature

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

