

HiFill® NY-75

Polyamide + Polyolefin

Techmer Engineered Solutions

Message:

HiFill® NY-75 is a Polyamide Polyolefin (Nylon Olefin) product. It is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific.

Features include:

ROHS certification

low hygroscopicity

General Information			
Features	Low hygroscopicity		
RoHS Compliance	RoHS compliance		
Appearance	Available colors		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.03	g/cm ³	ASTM D792
Molding Shrinkage - Flow (3.18 mm)	1.0 - 1.5	%	ASTM D955
Water Absorption (24 hr)	0.050 - 0.20	%	ASTM D570
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	54.8	MPa	ASTM D638
Tensile Elongation (Break)	5.0	%	ASTM D638
Flexural Modulus	2000	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	64	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT