

Europrene Lattice® 440

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Europrene Lattice 440 is an aqueous dispersion of a carboxylated styrene-butadiene copolymer obtained using synthetic anionic emulsifiers. It contains a non staining antioxidant

Key Features

Europrene Lattice 440 is specially designed for applications where an extremely low odour is required.

Main Applications

Europrene Lattice 440 is mainly used for adhesives. It is specially designed for applications where an extremely low odour is required.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Copolymer		
	Low to No Odor		
Uses	Adhesives		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	60.0	%	ASTM D5775
pH	8.0		ASTM D1417
Solids Content	50.0	wt%	ASTM D1417
Brookfield Viscosity ¹ (25°C)	300	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT