

# Aropol™ 8722

Thermoset Polyester

Ashland Performance Materials

## Message:

Ashland Resins for the Pultrusion Market

Chemistry

Flexibilizing resin

Performance Attributes

Blending resin for crack-free, thick parts. Used at levels near 20%.

Typical Applications

Thick parts.

General Information		
Features	Good Crack Resistance	
Uses	Blending	
	Thick-walled Parts	
Processing Method	Pultrusion	
Physical	Nominal Value	Unit
Solution Viscosity	650	mPa · s
Mechanical	Nominal Value	Unit
Tensile Modulus	1740	MPa
Tensile Strength	37.9	MPa
Tensile Elongation (Break)	31	%
Flexural Modulus	1460	MPa
Flexural Strength	55.2	MPa
Thermal	Nominal Value	Unit
Heat Deflection Temperature	42	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT