

MARPOL® EVA 28150

Ethylene Vinyl Acetate Copolymer

Marco Polo International, Inc.

Message:

MARPOL® EVA 28150 is a high flow Vinyl Acetate copolymer that has excellent compatibility with hydrocarbons, most waxes, and natural tackifiers. It is designed for making hot melt adhesives, sealants and wax blends.

General Information			
Features	High Flow		
Uses	Adhesives		
	Sealants		
Physical	Nominal Value	Unit	Test Method
Density	0.946	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.1 kg)	150	g/10 min	ASTM D1238
Vinyl Acetate Content	27.6	wt%	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	72		
Shore D	16		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	43.4	MPa	ASTM D638
Tensile Elongation (Break)	640	%	ASTM D638
Flexural Modulus - 1% Secant	13.1	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT