

Vinnolit® S 4080

Polyvinyl Chloride
Vinnolit GmbH & Co. KG

Message:

Vinnolit S 4080 is a specialty product for flexible PVC articles with excellent mechanical performance, primarily at elevated service temperatures.

General Information			
Features	High Heat Resistance		
Agency Ratings	EC 1907/2006 (REACH)		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.45	g/cm³	ISO 60
K-Value	80.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	168.0	ml/g	ISO 1628
Particle Size Distribution			ISO 4610
-- 1	< 1.0	%	
-- 2	> 95	%	
Volatile Matter	< 0.30	%	ISO 1269
Plasticiser Absorption (23°C)	34	%	ISO 4608
NOTE			
1.	retained on 0.250 mm screen		
2.	retained on 0.063 mm screen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT