

MTEGRITY™ LDPE LD400

Low Density Polyethylene

M. Holland Company

Message:

MTEGRITY™ LDPE LD400 is a Low Density Polyethylene product. It can be processed by injection molding and is available in North America. Applications of MTEGRITY™ LDPE LD400 include caps/lids/closures, electrical/electronic applications and household applications.

Characteristics include:

Good Processability

High ESCR (Stress Crack Resistant)

High Strength

General Information			
Features	Good Processability		
	High ESCR (Stress Crack Resist.)		
	Low Temperature Strength		
Uses	Closures		
	Electrical Parts		
	Household Goods		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.916	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	14	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	50		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	9.83	MPa	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Flexural Modulus	190	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	86.1	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

