

WPP PP WPP3208-FB BLK

Polypropylene Copolymer
Washington Penn Plastic Co. Inc.

Message:

WPP PP WPP3208-FB BLK is a Polypropylene Copolymer (PP Copolymer) product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Automotive.
Characteristics include:
Copolymer
Heat Stabilizer
Impact Resistant
Rigid

General Information			
Additive	Heat Stabilizer		
Features	Copolymer		
	Good Impact Resistance		
	Heat Stabilized		
	High Rigidity		
Uses	Automotive Applications		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.904	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	8.6	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	23.4	MPa	ASTM D638
Tensile Elongation (Break)	550	%	ASTM D638
Flexural Modulus - Tangent	1090	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	150	J/m	ASTM D256
Gardner Impact (23°C)	18.1	J	ASTM D3029

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT