

Delta ABS 8540-S

Acrylonitrile Butadiene Styrene

Delta Polymers

Message:

Delta ABS 8540-S is an Acrylonitrile Butadiene Styrene (ABS) product. It is available in North America.

Characteristics include:

Flame Rated

Flame Retardant

General Information			
Features	Flame Retardant		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.13	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	22	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	37.2	MPa	ASTM D638
Flexural Modulus	2210	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	260	J/m	ASTM D256
Flammability	Nominal Value	Test Method	
Flame Rating			UL 94
1.59 mm	V-0		
3.18 mm	V-0		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT