

# Integra™ M2433

Polypropylene Copolymer

PolySource, LLC

Message:

Integra™M2433 is a polypropylene copolymer (PP Copoly) material. This product is available in North America. Integra™The main characteristics of M2433 are: copolymer.

General Information			
Features	Copolymer		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (220°C/10.0 kg)	9.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus (23°C)	1310	MPa	ASTM D638
Tensile Strength (Yield, 23°C)	29.0	MPa	ASTM D638
Tensile Elongation (Yield)	12	%	ASTM D638
Flexural Modulus (23°C)	1070	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT