

KEP® 570P

Ethylene Propylene Diene Terpolymer

Kumho Polychem Co., Ltd.

Message:

Features:

High impact resistance in the modification of polyolefin thermoplastics (PP,PE)

Applications:

Blend with PP: injection moldings(bumper etc.), films, sheets and polyolefin modifiers, various types of automobile parts

General Information		
Features	High Impact Resistance	
Uses	Automotive Applications	
	Blending	
	Film	
	Plastics Modification	
	Sheet	
Forms	Pellets	
Processing Method	Injection Molding	
Physical	Nominal Value	Unit
Mooney Viscosity (ML 1+4, 125°C)	53	MU
Ethylene Content	70.0	wt%
Ethylidene Norbornene (ENB) Content	4.5	wt%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT