RTP 1203-55D

Thermoplastic Polyurethane Elastomer (Polyester)

RTP Company

Message:

Warning: The status of this material is 'Commercial: Limited Issue'

The data for this material has not been recently verified.

Please contact RTP Company for current information prior to specifying this grade.

-Preliminary Product Data per RTP Co.-

General Information				
Filler / Reinforcement	Glass Fiber,20% Filler by Weight			
RoHS Compliance	Contact Manufacturer			
Appearance	Black			
	Natural Color			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.30	g/cm³	ASTM D792	
Molding Shrinkage - Flow (3.18 mm)	0.10	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	965	МРа	ASTM D638	
Tensile Strength	37.9	МРа	ASTM D638	
Tensile Elongation (Break)	10	%	ASTM D638	
Flexural Modulus	621	МРа	ASTM D790	
Flexural Strength	18.6	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (3.18 mm)	480	J/m	ASTM D256	
Unnotched Izod Impact (3.18 mm)	No Break		ASTM D4812	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load			ASTM D648	
0.45 MPa, Unannealed	116	°C		
1.8 MPa, Unannealed	65.6	°C		
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity	1.0E+11	ohms·cm	ASTM D257	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating (1.59 mm)	НВ		UL 94	
Injection	Nominal Value	Unit		
Rear Temperature	182 to 210	°C		
Middle Temperature	182 to 210	°C		
Front Temperature	182 to 210	°C		

Mold Temperature	15.6 to 65.6	°C	
Injection Pressure	68.9 to 103	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

