SQUARE® LSG6931-50A/B

Silicone Rubber, LSR

Shenzhen SQUARE Silicone Co., Ltd.

Message:

Electronic encapsulation and heat-eliminating silicone gel

Product description

This product is one kind of 2-part liquid silicone rubber, catalyzed by platinum, mixing ratio of parts A:B=1:1; mainly suitable for euthermic electric parts PCB,CPU, MPU and LED heat-eliminating and encapsulation, with the features of high temperature-resistant and outstanding heat-eliminating.

Key Features

Oiltight, the fluidity and heat conduction property can be adjusted with requirement, non-toxic and eco-friendly.

Application

Suitable for electric parts encapsulation and heat-eliminating.

General Information			
Features	Environmental protection		
	Heat resistance, high		
	Non-toxic		
Uses	Encapsulant		
	Electrical/Electronic Applications		
Appearance	White-like		
Processing Method	Enclosure		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.55	g/cm³	ASTM D792
Thermal	Nominal Value	Unit	
Thermal Conductivity	3.0	W/m/K	
Thermoset	Nominal Value	Unit	
Thermoset Components			
Component a	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by weight: 1.0		
Shelf Life	52	wk	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

