

Kpren CM435

Chlorinated Polyethylene Elastomer

Shandong Xuye New Materials Co., Ltd.

Message:

Chlorinated polyethylene (CPE) is one of the leading products of Xuye new materials. The registered trademark is Kpren. The products cover all the important chlorinated polyethylene markets in both domestic and international.

Xuye Kpren CPE is high molecular synthetic material that produced by HDPE. It is white power, which is thermoplastic elastomer. It has the performances like: heat-resisting, weather-proof, oil resistance, inflaming retarding, chemical resistance, ozone resistance, etc. It can be used as impact modifier for PVC hard product, which is largely used in the production of plastics doors and windows and the production of tubing. It can also be used as special rubber to replace neoprene, used in electric wire and hose tape industries.

Xuye Kpren CPE is a low-energy, no pollution product. The use of this product plays an important role in the transform of traditional industries and the development of national economy.

Kpren CM435: Mooney viscosity is between 70 and 80 It has the advantages like: good mechanical property and easy processing, it is widely used in the production of wire, cable and sebific duct

General Information			
Features	Flame Retardant		
	Good Chemical Resistance		
	Good Processability		
	Good Weather Resistance		
	Medium Heat Resistance		
	Oil Resistant		
	Ozone Resistant		
Uses	Plastics Modification		
	Tape		
	Wire & Cable Applications		
Appearance	White		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Mooney Viscosity (ML 1+4, 125°C)	70 to 80	MU	ISO 289
Chlorine Content	33.0 to 37.0	wt%	ISO 1159
Volatile Matter	< 0.50	%	ISO 1269
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	< 57		ISO 7619
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 11.0	MPa	ISO 37
Tensile Elongation (Break)	> 700	%	ISO 37

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

