

Durez® 33934

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 33934 is a one-step liquid resin in a solution of butanol and aromatic solvents.

Durez 33934 is recommended for use in metal coating formulations for metal containers in food contact applications involving phenolic/epoxy coatings.

| General Information | | | |
|--------------------------|-------------------------|------|-----------------|
| Features | Food Contact Acceptable | | |
| Uses | Coating Applications | | |
| Forms | Liquid | | |
| Physical | Nominal Value | | Test Method |
| Color | 12 | | Internal Method |
| Viscosity - G&H; (125°C) | F | | Internal Method |
| Non-Volatile Content | 49 | % | Internal Method |
| Thermoset | Nominal Value | Unit | Test Method |
| Post Cure Time (150°C) | 0.025 | hr | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

