

Moplen HP400N

Polypropylene Homopolymer

LyondellBasell Industries

Message:

LyondellBasell Australia's Polypropylene grade HP400N is a high flow homopolymer with a conventional molecular weight distribution and is formulated with a general-purpose additive package. HP400N is designed for injection moulding applications where ease of flow is important.

General Information			
UL YellowCard	E151840-223801		
Features	Food Contact Acceptable		
	General Purpose		
	Good Stiffness		
	High Flow		
	Homopolymer		
Uses	Containers		
Agency Ratings	AS 2070-1999		
	FDA 21 CFR 177.1520(a) 1		
	FDA 21 CFR 177.1520(c) 1.1		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183/D
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	11	g/10 min	ISO 1133
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	73		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	32.0	MPa	ISO 527-2
Flexural Modulus	1400	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	2.5	kJ/m ²	ISO 180/1A
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature			
0.45 MPa, Unannealed	82.0	°C	ISO 75-2/B
1.8 MPa, Unannealed	51.0	°C	ISO 75-2/A
Vicat Softening Temperature	150	°C	ISO 306/A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT