

# Europrene Lattice® 5577

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

## Message:

Europrene Lattice 5577 is an aqueous anionic dispersion of a styrene-butadiene copolymer with high solid content obtained by emulsion polymerisation using fatty acid soap as emulsifier. It does not contain any antioxidant.

### Key Features

Europrene Lattice 5577, vulcanised, shows good mechanical properties. It can be used blended with natural latex

### Main Applications

Europrene Lattice 5577 is used for medium stiffness moulded foams, gel and no-gel carpet foams.

General Information			
Features	Copolymer		
	Foamable		
	Good Stiffness		
Uses	Blending		
	Foam		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	30.0	%	ASTM D5775
pH	10.5		ASTM D1417
Solids Content	66.0	wt%	ASTM D1417
Brookfield Viscosity <sup>1</sup> (25°C)	800	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT