

Ablebond 77-2LTC

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablebond 77-2LTC is an Epoxy; Epoxide (Epoxy) material. It is available in North America. Primary attribute of Ablebond 77-2LTC: Insulating.
Typical application of Ablebond 77-2LTC: Adhesives/Tapes

General Information			
Features	Electrically Insulating		
Uses	Adhesives		
Forms	Paste		
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	2.5E+14	ohms·cm	ASTM D257
Thermoset	Nominal Value	Unit	
Pot Life (23°C)	120000	min	
Shelf Life (5°C)	26	wk	
Demold Time			
100°C	15	min	
150°C	30	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT