

K-Prene 7000 XL 55

Thermoplastic Vulcanizate

Technovinyl Polymers India Ltd.

Message:

K-Prene 7000 XL 55 is a Thermoplastic Vulcanizate (TPV) material. It is available in Africa & Middle East. Primary attribute of K-Prene 7000 XL 55: Chemical Resistant.

Typical application of K-Prene 7000 XL 55: Handles

General Information			
Features	Alkali Resistant		
	Good Chemical Resistance		
	Soft		
Uses	Flexible Grips		
Appearance	Matte Finish		
	Translucent		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/5.0 kg)	4.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	50 to 60		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	2.50	MPa	ASTM D412
Tensile Elongation (Break)	450	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

