Taitarex® 861N / B / W

General Purpose Polystyrene

Taita Chemical Company, Ltd.

Message:

Taitarex® 861N / B / W is a General Purpose Polystyrene material. It is available in Asia Pacific or North America for injection molding. Important attributes of Taitarex® 861N / B / W are:

Flame Rated

Clarity

Good Dimensional Stability

Good Processability

Heat Resistant

Typical applications include:

Appliances

Consumer Goods

Electrical/Electronic Applications

Household Applications

General Information					
Features	General Purpose				
	Good Dimensional Stability				
	Good Processability				
	High Clarity				
	High Heat Resistance				
	Low Residuals				
Uses	Appliances				
	Audio Tapes				
	General Purpose				
	Household Goods				
	Toys				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.05	g/cm³	ASTM D542		
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	7.0	g/10 min	ASTM D1238		
Residual SM Monomer	300	ppm			
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield, 23°C, 3.18 mm)	44.1	MPa	ASTM D638		
Tensile Elongation (Break, 23°C, 3.18 mm)	2.0	%	ASTM D638		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact ¹ (23°C)	14	J/m	ASTM D256A		
Thermal	Nominal Value	Unit	Test Method		
Vicat Softening Temperature ²	100	°C	ASTM D1525 ³		
Flammability	Nominal Value		Test Method		

Flame Rating (1.59 mm)	НВ	НВ		
Optical	Nominal Value	Unit		
Haze (2800 μm)	0.40	%		
NOTE				
1.	1/4"x1/2"x5/2"	1/4"x1/2"x5/2"		
2.	3 mm thick	3 mm thick		
3.	Rate B (120°C/h), Loading	Rate B (120°C/h), Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

