

apirex® MBL 35 UV

Thermoplastic Polyurethane Elastomer (Polyether)

API SpA

Message:

apirex® MBL 35 UV is a thermoplastic polyurethane elastomer (polyether)(TPU-polyether) product. It can be processed by coating and is available in Europe. apirex® MBL 35 UV applications include textile/fiber, industrial applications and conveyor belts.

General Information			
Uses	Conveyor		
	Textile applications		
	Industrial application		
Processing Method	Coating		
Physical	Nominal Value	Unit	
Viscosity (23°C)	250 - 400	Pa · s	
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
--	> 7.00	MPa	ASTM D638
100% strain	> 3.00	MPa	ASTM D638
Tensile Elongation (Break)	> 180	%	ASTM D638
Additional Information			

Crosslinker Apicell L2 for 100pbw of Apirex: 11

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

