# Braskem PE HDB6050

## High Density Polyethylene

#### Braskem IDESA

### Message:

HDB6050 is a high molecular weight copolymer grade developed for the production of medium-large blow molded articles. Provides excellent processability, good rigidity, high impact strength, outstanding chemical resistance and high ESCR.

High performance blow molded containers typically 20-240 liters (5.3 63.4 gallons) capacity for packaging aggressive products; especially where approvals are required to UN recommendations for Dangerous Goods and RID/ADR Compatibility testing.

Process:

Blow Molding

General Information			
Features	Good Rigidity		
	High ESCR (Stress Cracking Resistance)		
	High molecular weight		
	Copolymer		
	Impact resistance, high		
	Workability, good		
	Good chemical resistance		
Uses	Blown Containers		
	Packaging		
	Blow molding applications		
	Container		
Processing Method	Blow molding		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/21.6			
kg)	6.0	g/10 min	ISO 1133
Environmental Stress-Cracking Resistance			ASTM D1693
50°C, 10% Adinol	500	hr	ASTM D1693
50°C, 100% Adinol	> 1000	hr	ASTM D1693
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	26.0	MPa	ISO 527-2
Tensile Strain (Break)	> 500	%	ISO 527-2
Flexural Modulus	1000	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength	No Break		ISO 179
Additional Information	Nominal Value	Unit	
Bottle Stress Crack Resistance (60°C)	8.3	day	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

