# SILPURAN® 6000/05 A/B

### Silicone

### Wacker Chemie AG

### Message:

Silicone Rubber, LSR
Gaskets, Plastics and Rubber Processing
Masks, Pharmaceuticals & Healthcare
Membranes, Pharmaceuticals & Healthcare
Seals (HealthCare / Pharma), Pharmaceuticals & Healthcare
Valves (HealthCare / Pharma), Pharmaceuticals & Healthcare

General Information	
Features	Biocompatible
	BPA Free
	Breathable
	Good Chemical Resistance
	Good Flexibility
	Good Sterilizability
	Good Thermal Stability
	High Gas Permeability
	High Heat Resistance
	High Purity
	Low to No Odor
	Low to No Water Absorption
	Non-Toxic
	Steam Resistant
Uses	Body Implants
	Medical Devices
	Medical/Healthcare Applications
	Pharmaceuticals
Agency Ratings	ISO 10993
	USP Class VI
Processing Method	Injection Molding
	Liquid Injection Molding (LIM)

Uncured Properties	Nominal Value	Unit	Test Method
Color	Clear/Transparent		
Density	1.04	g/cm³	ISO 1183
Viscosity	21	Pa·s	DIN 53019

Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	5		DIN 53505
Tensile Strength	2.50	MPa	DIN 53504
Tensile Elongation at Break	700	%	DIN 53504
Tear Strength	7.80	kN/m	ASTM D624B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

