

Magnobond 8000

Epoxy; Epoxide
Magnolia Plastics, Inc.

Message:

Magnobond 8000 is an Epoxy; Epoxide (Epoxy) product filled with 80% silver. It is available in North America. Typical application: Adhesives/Tapes.

Characteristics include:

Conductive

Low Viscosity

General Information			
Filler / Reinforcement	Silver,80% Filler by Weight		
Features	Electrically Conductive		
	Low Viscosity		
Uses	Adhesives		
Forms	Liquid		
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	4.3E-4	ohms · cm	ASTM D257
Thermoset	Nominal Value	Unit	
Thermoset Components			
Hardener	Mix Ratio by Weight: 3.0		
Resin	Mix Ratio by Weight: 100		
Pot Life (25°C)	30	min	
Shelf Life	26	wk	
Demold Time			
25°C	1400 to 2900	min	
80°C	60 to 120	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT