

TYMAX® GT4525

Linear Low Density Polyethylene

Westlake Chemical Corporation

Message:

Westlake GT4525 is an anhydride modified linear low density polyethylene designed for blown film extrusion that contains no slip and no antiblock additives. This resin is designed to function as a coextruded tie layer in multilayer film applications. Westlake GT4525 is designed to tie polyethylene to resins that typically have poor bonding characteristics such as polyamide and EVOH.

Application/Uses

Blown Film

Packaging

Tie-layer

General Information			
Uses	Blown Film		
	Films		
	Multilayer film		
	Bonding resin		
Processing Method		Blow film	
Physical	Nominal Value	Unit	Test Method
Density	0.912	g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.75	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	92.2	°C	ASTM D1525
Peak Melting Temperature	121	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT