ESENTTIA 20H10NA

Polypropylene Homopolymer

Polipropileno del Caribe S.A.

Message:

Characteristics: Control reologhy high melt flow rate Homopolymer polypropylene, easy mold filling, good stiffness/impact balance,, with nucleant and antistatic additives.

Recommended for: Injection molding of thin wall rigid containers, fast cycle time, cover electrical appliances, closures, general purpose injection molding applications.

General Information				
Additive	Antistatic			
	Nucleating Agent			
Features	Antistatic			
	Controlled Rheology			
	Fast Molding Cycle			
	Food Contact Acceptable			
	General Purpose			
	High Flow			
	High Rigidity			
	Homopolymer			
	Nucleated			
Uses	Appliances			
	Closures			
	General Purpose			
	Thin-walled Containers			
Agency Ratings	EC 1907/2006 (REACH)			
	EC 1935/2004			
	EC 2023/2006			
	EU 10/2011			
	FDA 21 CFR 177.1520(a)(3)(i)(c)(1)			
	FDA 21 CFR 177.1520(b)			
	FDA 21 CFR 177.1520(c) 3.1a			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Melt Mass-Flow Rate (MFR) ¹ (230°C/2.16				

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ² (Yield, 3.20 mm,			
Injection Molded)	35.9	MPa	ASTM D638
Tensile Elongation ³ (Yield, 3.20 mm,			
Injection Molded)	9.0	%	ASTM D638
Flexural Modulus - 1% Secant ⁴ (3.20 mm,			
Injection Molded)	1590	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.20 mm,			
Injection Molded)	37	J/m	ASTM D256A
NOTE			
1.	Procedure B		
2.	Type I, 50 mm/min		
3.	Type I, 50 mm/min		
4.	Type I, 1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

