

Axiall PVC FG-9229

Rigid Polyvinyl Chloride

Axiall Corporation

Message:

FG-9229 is a rigid blow molding, food-grade PVC compound with excellent optical and processing characteristics. FG-9229 is suitable for use in a variety of food, cosmetic and general purpose packaging applications.

General Information			
Features	Rigidity, high		
	Optical		
	Workability, good		
	Compliance of Food Exposure		
Uses	Cosmetic Packaging		
	Packaging		
	Food packaging		
Processing Method	Blow molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30 - 1.34	g/cm ³	ASTM D792
PVC Cell Classification	16343		ASTM D1784
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2690	MPa	ASTM D638
Tensile Strength	43.4	MPa	ASTM D638
Flexural Strength	79.3	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm)	960	J/m	ASTM D256
Tensile Impact Strength	185	kJ/m ²	ASTM D1822
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	60.0	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT