# Tarflen® SM-K22G3

## Polytetrafluoroethylene

## Grupa Azoty S.A.

# Message:

Tarflen® SM-K22G3 is a polytetrafluoroethylene (PTFE) material, which contains 22% coke filler and 3.0% graphite fiber reinforced material. This product is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific.

Tarflen® The main features of the SM-K22G3 are:

Flame Retardant good weather resistance

chemical resistance

Wear-resistant

Typical application areas include: engineering/industrial accessories

application of coating

Wire and cable

Sealing applications

Hose

General Information					
Filler / Reinforcement	Coke filler, 22% filler by weight  Graphite fiber reinforced material, 3.0% filler by weight				
Features	Low friction coefficient				
	Moisture proof				
	Good chemical resistance				
	Good wear resistance				
	Good weather resistance				
	Flame retardancy				
Uses	Cable sheath				
	Washer				
	Valve/valve components				
	Pipe				
	Piping system				
	Seals				
	Accessories				
	Coating application				
	Fabric coating				
Forms	Particle				
Physical	Nominal Value	Unit	Test Method		
Density	2.11	g/cm³	ISO 1183		
Molding Shrinkage			ISO 294-4		
Vertical flow direction	2.0 - 3.5	%	ISO 294-4		

Flow direction	3.0	%	ISO 294-4
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	14.0	МРа	ISO 527-2
Tensile Strain (Break)	100	%	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Linear thermal expansion coefficient			ISO 11359-2
Flow: 23 to 100°C	1.2E-4	cm/cm/°C	ISO 11359-2
Lateral: 23 to 100°C	7.0E-5	cm/cm/°C	ISO 11359-2
Extrusion instructions			

Molding Pressure: 40 to 60 MpaMolding Temperature: 370 °C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

