

ICORENE® N2309

Linear Low Density Polyethylene

ICO Polymers EMEA, A Division of A. Schulman

Message:

ICORENE® N2309 is a premium quality adhesion modified linear low density polyethylene suitable for general purpose use. This grade is supplied as a powder for use in processes such as masterbatch production.

General Information			
Features	Good Adhesion		
	Good Processability		
Uses	Masterbatch		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Density	0.930	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	24	g/10 min	ASTM D1238
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	103	°C	ISO 306 ¹
Peak Melting Temperature	124	°C	ISO 11357-1, -2, -3
NOTE			
1.	Rate A (50°C/h), Loading 1 (10 N)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

