

Fainplast PVC GK 89/R

Flexible Polyvinyl Chloride

Fainplast Compounds S.r.l

Message:

Fainplast PVC GK 89/R is a Flexible Polyvinyl Chloride product. It is available in Africa & Middle East, Asia Pacific, Latin America, or North America. Typical application: Wire & Cable.

Characteristics include:

Flame Retardant

Chemical Resistant

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
	Hydrocarbon Resistant		
Uses	Wire & Cable Applications		
Wire Types	RZ		
Agency Ratings	EN 50363-0		
Physical	Nominal Value	Unit	Test Method
Density	1.39 to 1.43	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	87 to 91		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 17.0	MPa	ISO 527-2
Tensile Strain (Break)	> 240	%	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Cold Flexibility	-19 to -15	°C	ISO 458/2
Thermal Stability	> 35	min	CEI 20-34/3-2
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	31 to 33	%	ISO 4589-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT