

Regis® E6542

Polyolefin

Noble Polymers

Message:

350,000psi Flexural Modulus TPO for Extrusion and Blow Molding

Regis Thermoplastic Polyolefin (TPO) compounds provide a unique balance of physical properties and ease of processing. Regis' full range of flexural modulus, impact and other physical property options allows you to customize a solution to meet your specific application's needs.

Regis compounds are used in the automotive and heavy truck industries for applications such as side fairings, bumper covers, rocker panels, air inlet panels and other applications that require a balance of durability and processability.

Features Include:

Flexural modulus range from 35,000 - 350,000 psi

Available in natural, black or custom colors

Additive packages include: UV stabilization, scratch and mar resistance

Can be formulated utilizing reprocessed base materials

Formulations for injection molding as well as profile and sheet extrusion

Customized formulations available to meet your specific need

All Regis products are 100% recyclable

General Information	
Features	Recyclable Material
Uses	Automotive Applications
	Automotive Bumper
Appearance	Black
	Colors Available
	Natural Color
Processing Method	Extrusion
	Profile Extrusion
	Sheet Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.10	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.5	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	25.5	MPa	ASTM D638
Flexural Modulus	2410	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	430	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

