

# Nipol® 1472X

Acrylonitrile Butadiene Rubber

Zeon Chemicals L.P.

## Message:

NIPOL® NITRILE ELASTOMERS (NBR) are recommended when oil or solvent resistance is needed for the proper functioning of rubber parts. Nipol nitrile elastomers are available in a broad range of acrylonitrile content to ensure optimal performance in a variety of conditions. As acrylonitrile content is increased, fuel, oil and solvent resistance improve; low-temperature flexibility and resiliency are improved as butadiene content increases. To obtain a broad spectrum of hardnesses and other essential properties, Nipol elastomers can be blended to achieve optimal performance. Nipol elastomers are the best value for all but the most demanding oil, heat and chemical applications and are available in powder, crumb, liquid and bale forms. Nipol nitrile elastomers are especially suitable for thermoplastics and thermoset modification; they are also used as additives in coatings and adhesives.

### Special Properties/Applications

Carboxylated nitrile crumb, used in epoxy modification, for adhesives and composites. Contains talc partitioning agent. Crumb version of Nipol 1072CGX.

General Information	
Filler / Reinforcement	Talc
Features	Oil Resistant
	Solvent Resistant
Uses	Additive
	Adhesives
	Plastics Modification
Forms	Bale
	Crumb
	Liquid
	Powder

Physical	Nominal Value	Unit	
Mooney Viscosity <sup>1</sup>	22 to 35	MU	
ACN Content	27	%	
Viscosity - Cement	100 to 1500	mPa · s	
Median Particle Size	9.50	mm	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-31.0 to -18.0	°C	DSC
NOTE			

1. Measured on the base nitrile portion.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

