ADENE® N09CTE-00

Polypropylene Homopolymer

A.D. Compound S.p.A.

Message:

PP Homopolymer Natural 50% Mineral filled

General Information				
Filler / Reinforcement	Mineral filler, 50% filler l	Mineral filler, 50% filler by weight		
Recycled Content	Yes			
Features	Homopolymer			
Appearance	Natural color			
Processing Method	Injection molding			
Physical	Nominal Value	Unit	Test Method	
Density	1.36	g/cm³	ISO 1183	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	15	g/10 min	ISO 1133	
Mechanical	Nominal Value	Unit	Test Method	
Flexural Modulus	2000 - 2500	MPa	ISO 178	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	2.5 - 3.5	kJ/m²	ISO 180/1A	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

