

Pujie CPE-8090

Chlorinated Polyethylene

Zhanhua Pujie Chemical Technology Co.,Ltd

Message:

CPE-8090 is Lower molecular weight than 135A, better processibility, suitable for higher speed extrusion.

General Information		
Features	Low molecular weight	
	Workability, good	
Uses	Catheter	
	Piping system	
	Doors and Windows	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Apparent Density	> 0.50	g/cm ³
Chlorine Content	34.0 - 36.0	wt%
Sieve Residue - 40 Mesh	> 98.0	
Heat of Fusion		J/g
Impurities		pcs/50 g
Whiteness - E457	> 90.0	°
Volatiles		%
Thermal Decomposition Temperature	> 170	°C
Hardness	Nominal Value	Unit
Durometer Hardness (Shore A)	< 58	
Mechanical	Nominal Value	Unit
Tensile Strength	> 8.00	MPa
Tensile Elongation (Break)	> 700	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT