

Stirol UPM-424 (1s.)

High Impact Polystyrene
JSC CONCERN STIROL

Message:

UPM-424 is for manufacturing of sheets, inside details for refrigerators (except chambers with operating mode below minus 18°C and with polyurethane foam heat insulation).

General Information	
Features	Good Thermal Stability
	High Impact Resistance
Uses	Appliance Components
	Sheet
Forms	Granules
Processing Method	Die Molding
	Extrusion

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) ¹	3.0 to 5.3	g/10 min	ISO 1133
Water Absorption (Equilibrium, 23°C, 50% RH)	< 0.10	%	ISO 62
Bound Styrene	< 0.1	%	
Ash Content	> 1.1	%	
Rubber Content	10.0		

Mechanical	Nominal Value	Unit	Test Method
Tensile Strain (Break)	> 35	%	ISO 527-2

Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	> 7.4	kJ/m²	ISO 179

NOTE	
1.	±13%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT