

# SKYBOND® 2595

Aromatic Polyimide

Industrial Summit Technology Co.

## Message:

The Skybond® product line encompasses a number of products usable as matrix resins for manufacture of high thermal stability structural composites. Composites based on the Skybond® family of resins have continuous use temperatures in excess of 600° F with short term capability greater than 1000° F. Prepreg has been successfully manufactured from all common high performance substrates, such as, E-glass, high modulus carbon, and quartz. Two new classes of matrix resins have been developed in the Skybond® family. The first can be processed by RTM molding techniques to bring the outstanding thermal resistance of polyimide resins to RTM molded composites. The second new class of Skybond® matrix resins is the two-stage cure resins that when used in prepreg applications allow the manufacture of very low void level composites by autoclave processing (<0.5% voids) combined with excellent thermal stability of polyimide resins.

General Information		
Features	Good Thermal Stability	
Uses	Compounding	
Physical	Nominal Value	Unit
Density	1.10 to 1.13	g/cm <sup>3</sup>
Solution Viscosity	1000 to 3000	mPa·s
Solids Content	48 to 50	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT