

SynPlast™ L9TM-E

Triisononyl Trimellitate

PolyOne Corporation

Message:

Linear & branched nonyl trimellitate

General Information			
Uses	Electrical/Electronic Applications		
	Industrial application		
	Application in Automobile Field		
	Ceiling compartment cable sheath material		
	Additive		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	0.965 - 0.973	g/cm ³	ASTM D792
Acid Value - (as % TMA)		%	ASTM D1045
Moisture Content		ppm	ASTM E203
Appearance	Clear, clean		
Color-(Pt-Co Scale)			ASTM D1209
Ester content	> 99	%	ASTM D3465
Casting point	-54	°C	ASTM D97
Additional Information			
Contains 0.1-0.15 wt% 1,1,3-Tris (2-methyl-4-hydroxy-5-t-buytl phenyl) butane as an antioxidant			
NOTE			

1. @ 25 C/25 C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT