ELASTOSIL® R 401/50

Silicone

Wacker Chemie AG

Message:

Silicone Rubber, HTV

Spark Plugs Boots, Automotive & Transportation

Vibration Dampers, Automotive & Transportation

Hoses, Automotive, Automotive & Transportation

Protective Clothing, Technical Textiles

Exhaust-Pipe Suspensions, Automotive & Transportation

Molded Seals, Plastics and Rubber Processing

Membranes, Automotive & Transportation

Molded Parts, Automotive, Plastics and Rubber Processing

Molded Parts, Food Contact, Plastics and Rubber Processing

Molded Parts, Technical, Plastics and Rubber Processing

Molded parts; tap water and wastewater contact, Plastics and Rubber Processing

Extrudates, Automotive, Plastics and Rubber Processing

Extrudates, food contact, Plastics and Rubber Processing

Extrudates, Technical, Plastics and Rubber Processing

Extruded parts; tap water and wastewater contact, Plastics and Rubber Processing

Coating of Fabrics and Textiles, Technical Textiles

Sealant Profiles, Construction

General Information	
UL YellowCard	E75704-101818639
Features	Food Contact Acceptable
	General Purpose
Uses	Automotive Applications
	Compounding
	Gaskets
	Potable Water Applications
	Profiles
	Seals
	Valves/Valve Parts
	Wire & Cable Applications
Processing Method	Calendering
	Compression Molding
	Extrusion
	Press Molding
	Profile Extrusion

Uncured Properties	Nominal Value	Unit	Test Method	
Color	Clear/Transparent			
Density	1.15	g/cm³	ISO 1183	

Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	52		DIN 53505
Tensile Strength	11.0	MPa	DIN 53504
Tensile Elongation at Break	520	%	DIN 53504
Compression Set	34	%	DIN ISO 815-B
Tear Strength	25.0	kN/m	ASTM D624B
Rebound Resilience	53	%	DIN 53512

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

