

Generic PP Elastomer

Propylene Elastomer

Generic

Message:

This data represents typical values that have been calculated from all products classified as: Generic PP Elastomer
This information is provided for comparative purposes only.

General Information			
Physical	Nominal Value	Unit	Test Method
Density	0.859 to 0.878	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.1 to 9.1	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Break, 23°C	5.45 to 17.2	MPa	
23°C	1.81 to 5.65	MPa	
Tensile Elongation (Break, 23°C)	1900 to 2000	%	ASTM D638
Flexural Modulus (23°C)	8.85 to 13.9	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT