# **MAJORIS BGR310 - 8229**

### Polypropylene

#### AD majoris

#### Message:

MAJORIS BGR310-8229 is a polypropylene product, which contains a 30% glass fiber reinforced material. It can be processed by injection molding and is available in Europe.

Features include:

flame retardant/rated flame environmental protection/green

General Information			
Filler / Reinforcement	Glass fiber reinforced material, 30% filler by weight		
Features	Recyclable materials		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	1.12	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	2.0 - 8.0	g/10 min	ISO 1133
Molding Shrinkage	0.40 - 0.70	%	
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus <sup>1</sup>	5700	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength			ISO 179/1eA
-20°C	5.0	kJ/m²	ISO 179/1eA
23°C	6.0	kJ/m²	ISO 179/1eA
Charpy Unnotched Impact Strength (23°C)	22	kJ/m²	ISO 179/1eU
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa,			
Unannealed)	159	°C	ISO 75-2/B
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94
Injection	Nominal Value	Unit	
Drying Temperature	90.0	°C	
Drying Time	4.0	hr	
Processing (Melt) Temp	230 - 270	°C	
Mold Temperature	30.0 - 70.0	°C	
Injection Rate	Slow-Moderate		
Injection instructions			
Holding pressure: 50 to 70% of the injection	pressure		
NOTE			
1.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

